

## ***Product Overview***



### **Uses:**

- Aiming of headlamp and fog lamp reflectors
- Difficult to reach areas
- Replace difficult to assemble gear boxes used to move adjuster access location

### **Benefits:**

- Simple attachment method at original access point - E5 or 6 mm external hex drive
- Cable can be incorporated with a right angle adjuster, eliminating a second part number
- Solves difficult to reach access point issues for aiming
- Design assistance available for allowable bend radius and recommended mounting points

### **Specifications:**

- Cable assembly Drive withstands 1.7 Nm (15 in-lb) Static Torque
- Minimum pull off force of 35.6 N (8 lbf) installed condition
- Cable Material in Stainless (externally mounted applications) or Low Carbon Steel (internally mounted applications)
- Minimum bend radius of 60.0 mm
- Multiple input and output drives available
- Multiple cable lengths available

# **ASYST**

#### **NORTH AMERICA**

Ethan Warner  
Regional Sales & Application Engineer  
5811 99th Ave.  
Kenosha, WI 53144—USA  
Phone: +1-765-246-2323  
Email: [ewarner@asysttech.com](mailto:ewarner@asysttech.com)

# ***Cable Adjusters***

Rev. Date 08April24

## ***Cable Standard Input and Output Drives***



Plastic Hex with O-Ring Seal

Plastic Coupler with E5 Torx



Plastic Funnel with Hex & P2 Drive

Plastic 6mm External Hex



Die Cast Input Drives

Assembled to Right Angle Adjuster

# **ASYST**

### **NORTH AMERICA**

Ethan Warner  
Regional Sales & Application Engineer  
5811 99th Ave.  
Kenosha, WI 53144—USA  
Phone: +1-765-246-2323  
Email: [ewarner@asysttech.com](mailto:ewarner@asysttech.com)